

M-LINE SUSPENDED & SURFACE SYSTEM





Construction

The suspended and surface system utilises the same profile and is available in standard lengths up to 2824mm with bespoke lengths available to order. Surface mounting is achieved by directly fixing through the rear of the profile. Suspension is made simple using a single-point ceiling bracket with 2m adjustable stainless steel wire system. Uplighting is available on lengths from 584mm upwards.

Typical Applications

General Office Areas, Conference Rooms, Reception Areas, Educational Facilities, Retail Units, Bars, Restaurants, Hotels and Leisure Facilities, and Residential Properties.

- // Aluminium extruded sections in 9 standard lengths
- // Bespoke lengths available in 140mm increments
- // Colour options in 3000K/4000K/5000K
- // Custom shapes available subject to design
- // Incorporates European branded LED drivers
- // Direct/Indirect lighting options available for suspended fittings
- // Utilises latest generation long-life LEDs from leading manufacturers
- // Clip-in gear tray for easy installation
- // Opal polycarbonate diffuser
- // Tuneable white and RGB options available
- // Dimmable and emergency options available
- // Compatible with eBlue wireless switching system
- // Dual Switch option available
- // CRI>80, 50,000h life
- // 5 year warranty





LIGHTING THE WAY

M-LINE SUSPENDED & SURFACE SYSTEM



Product Code	Description	Length	Colour Temperature	Lumen Output	LED Wattage
Suspended Direct Lighting System					
MLE584	Suspended Direct Light Only	584mm	4000K	1135	12W
MLE864	Suspended Direct Light Only	864mm	4000K	1702	19W
MLE1144	Suspended Direct Light Only	1144mm	4000K	2270	25W
MLE1424	Suspended Direct Light Only	1424mm	4000K	2837	31W
MLE1704	Suspended Direct Light Only	1704mm	4000K	3405	37W
MLE1984	Suspended Direct Light Only	1984mm	4000K	3973	43W
MLE2264	Suspended Direct Light Only	2264mm	4000K	4540	50W
MLE2544	Suspended Direct Light Only	2544mm	4000K	5107	56W
MLE2824	Suspended Direct Light Only	2824mm	4000K	5675	62W
NOTE: Includes 2m suspension kits (longer bespoke lengths available in 140mm increments)					
Suspended Direct/Indirect Lighting System/70% Direct/30% Indirect					
MLE584/DIR/IND	Suspended Direct/Indirect Light	584mm	4000K	1469	19W
MLE864/DIR/IND	Suspended Direct/Indirect Light	864mm	4000K	2369	31W
MLE1144/DIR/IND	Suspended Direct/Indirect Light	1144mm	4000K	3271	43W
MLE1424/DIR/IND	Suspended Direct/Indirect Light	1424mm	4000K	4172	56W
MLE1704/DIR/IND	Suspended Direct/Indirect Light	1704mm	4000K	5073	68W
MLE1984/DIR/IND	Suspended Direct/Indirect Light	1984mm	4000K	5974	81W
MLE2264/DIR/IND	Suspended Direct/Indirect Light	2264mm	4000K	6875	93W
MLE2544/DIR/IND	Suspended Direct/Indirect Light	2544mm	4000K	7775	105W
MLE2824/DIR/IND	Suspended Direct/Indirect Light	2824mm	4000K	8677	118W
NOTE: Includes 2m suspension kits (longer bespoke lengths available in 140mm increments)					
Surface Mounted System					
MLES584	Surface Direct Light Only	584mm	4000K	1135	12W
MLES864	Surface Direct Light Only	864mm	4000K	1702	19W
MLES1144	Surface Direct Light Only	1144mm	4000K	2270	25W
MLES1424	Surface Direct Light Only	1424mm	4000K	2837	31W
MLES1704	Surface Direct Light Only	1704mm	4000K	3405	37W
MLES1984	Surface Direct Light Only	1984mm	4000K	3973	43W
MLES2264	Surface Direct Light Only	2264mm	4000K	4540	50W
MLES2544	Surface Direct Light Only	2544mm	4000K	5107	56W
MLES2824	Surface Direct Light Only	2824mm	4000K	5675	62W

For more information, call us on 01582 369005 or email sales@mountlighting.co.uk

M-LINE SUSPENDED & SURFACE SYSTEM



Suspended Direct/Indirect System



Surface Mounted System

Control Options

Option Code	Description
/M	3 Hour Maintained Emergency
/MZ	3 Hour Maintained DALI Emergency
/D	1-10V Driver
/DALI	DALI/DSI Dimmable Driver
/3K	3000K LED
/5K	5000K LED
RGB	Colour Changing LED

Suspension Options

Option Code	Description
Supply Cable	
CABTR3C	1.5m Transparent Current Cable 3 x 0.75mm ²
CABTR5C	1.5m Transparent Current Cable 5 x 0.75mm ²
MLESUS	2m Suspension kit for suspended M-Line
NOTE: Alternative length suspension kits available - POA	

Colour Options

Option Code	Description
/W	White (RAL 9016)
/G	Grey (RAL 9006)
/B	Black (RAL 9005)
/U (POA)	Blue (RAL 5002)
/V (POA)	Green (RAL 6018)
/T (POA)	Yellow (RAL 1021)
/K (POA)	Red (RAL 3020)
/N (POA)	Jungle
/D (POA)	Goldeneye
/O (POA)	Sahara
/L (POA)	Autumn
/R (POA)	Rusty chain
/C (POA)	Pure chocolate
/I (POA)	Mist
/9 (POA)	Darkrock
/I (POA)	Carbon



CABTR3C




CLIP-IN GEAR TRAY



CABTR5C



MLESUS



Typical Suspension and Cable Entry Points

