



LED

Norms: EN 60598-1, EN 60598-2-2



PRODUCT DESCRIPTION

**Areas of Application:** Public buildings, Housing, Offices, Hotel and Restaurant services, Art and Culture spaces.

**Mounting:** Wall Mounted.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>80, 75.000h life (@L90, B10, Ta 25°C).

**Optical System:** Lens in PMMA and Polycarbonate Diffuser.

**Control Gear:** LED driver, 220-240VAC-50/60Hz.

**Materials:** Body: Steel sheet and extruded aluminium tube.

**Surface Finish:** Powder coated.

Direct

	LED	UGR	W	Lm	η(%)	AxBxCxDxE(mm)		kg	ORDER CODE
		16	5	240	95	95x170x57x30x80	122x74x57	1	90089.L003.E

- To complete the product add optical system. Please order separately.
- The technical data represent rated values for an 47° optic lens.

Example code for order: 90089.L003.E (ORDER CODE) + W(COLOUR/FINISH) + 926200 + SENSOR + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

**COLOUR / FINISH**


Code	Description
 W	White
 G	Grey
 B	Black
 U	Blue
 V	Green
 T	Yellow
 K	Red
 O	Sahara
 L	Autumn
 D	Golden eye
 R	Rusty chain
 C	Pure chocolate
 N	Jungle
 1	Mist
 9	Dark rock
 I	Carbon

**DIMENSIONS**



**OPTIONS**

**Optical system**



14° Lens  
47° Lens  
Oval Lens

Order Code  
**926200**  
**926201**  
**926202**

**ON/OFF Sensor**



ON/OFF Sensor

Order Code  
**SENSOR**

**Colour temperature**



2700K

Order Code  
**2000**

**DETAILS**



14° optical lens light effect



47° optical lens light effect



Light effect with oval lens



Lens fixing system detail

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY



**TO SPECIFY:**  
Orientable (0°-90° vertically and 0°-355° horizontally) LED wall mounted fitting. Steel sheet body and extruded aluminium tube. Standard version 4000K, CRI>80 and 75.000h lifetime LED (@L90, B10, Ta 25°C) and ON/OFF button. Possibility of choosing different beam angles (14°/47°/oval), which combined with opal diffuser gives high visual comfort. Available with ON/OFF sensor and colour temperatures 2700K as options. Available in 16 different colours. - as Roxo Lighting GLAM /WE.

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.