

## CANTA

### Surface/Suspended Pendant Light

- // Surface/Suspended luminaire with options for track lighting
- // UGR>19 can be achieved with narrower beam angles
- // Beam angle 60° as standard, options for 24° or 36°
- // High-quality powder-coated aluminium
- // 3000K option
- // CRI>80 as standard, CRI>90 option available
- // IP20
- // Flex length can be adjusted
- // Compatible with Casambi wireless control system
- // 5-year warranty



### Construction

Our CANTA luminaire has been designed as a stylish option for surface, track or suspended applications and is ideal where appearance is important.

The body is powder-coated aluminium and gives good heat dissipation. The faceted reflector has a good reflective rate.

### Typical Applications

Hospitality, Tea Points, Seating, Reception and Leisure Areas.

### Size Options


#### Ceiling Rose



#### Body



Product Code	Size (A)	Size (B)
CAN10	Ø65mm	180mm
CAN15	Ø85mm	206mm
CAN25	Ø100mm	220mm



Product Code	LED Wattage	Lumen Output	Lumen/Watt	Colour Temperature	Beam Angle
CAN10	10W	1244	121	4000K	60°
CAN15	15W	1822	126	4000K	60°
CAN25	25W	3006	126	4000K	60°

Replace CAN with CANS for surface mount option

Section	Option Code	Description
1 - CONTROL	/ DALI	DALI Dimmable Driver
	/ BTC	Casambi Dimmable Driver
2 - COLOUR FINISH	/ BK	Black
	/ WH	White
3 - CCT	/ 4K	4000K LED
	/ 3K	3000K LED (light output -3%)
4 - BEAM ANGLE	/ R24	24 degree lens (light output -1%)
	/ R36	36 degree lens
	/ R60	60 degree lens
5 - CRI	/ 80	CRI>80
	/ 90	CRI>90 (light output -15%)

For optional features, please include the option code suffix with the product code when ordering.