

ENFORCE

Low UGR Surface/Suspended LED Downlight

- // Incorporates Tridonic LED and driver system
- // Multi-faceted 60° reflector as standard
- // Finished in RAL 9016 brilliant white as standard
- // Black and grey options available
- // 3000K and 4000K options
- // Integral emergency option
- // Dimming options available
- // Surface as standard (suspension mounting available)
- // IP20
- // CRI>80
- // 5-year warranty
- // Manufactured in UK




Construction

Our low glare, UGR19 compliant Enforce downlight has been selected for use in surface or suspended mounted applications and can be mounted directly onto a ceiling or BESA box. The powder-coated aluminium body provides corrosion resistance and excellent heat dissipation. The high-quality reflector is sealed by a clear diffuser. The size of the fitting allows for integral emergency controls.

Typical Applications

Amenity Areas, Toilets, Tea-Points, Canteens, Receptions and General Office and Breakout Areas.


Size Options



Size

Ø 150mm

H 165mm



Product Code	LED Wattage	Lumen Output	Lumen/Watt	Colour Temperature
ENF8/3K	8W	1010	126	3000K
ENF8	8W	1044	130	4000K
ENF14/3K	14W	1705	124	3000K
ENF14	14W	1766	128	4000K
ENF19/3K	19W	2307	121	3000K
ENF19	19W	2385	125	4000K

Option Code	Description
/M	3-Hour Maintained Emergency
/MZ	3-Hour Maintained DALI Emergency
/TD	Mains Dimmable
/DALI	DALI/DSI Driver
/BTC	Casambi Dimmable
/TW	Tuneable White
/MF25	25° Multi-Faceted Reflector
/MF40	40° Multi-Faceted Reflector
/SP40	40° Specular Reflector
/SA50	50° Satin Reflector
/9005	RAL 9005 (Black)
/9006	RAL 9006 (Grey)
/9010	RAL 9010 (White)
/SUS	Suspended Option

For optional features, please include the option code suffix with the product code when ordering.