

## ENFORCE

### Low UGR Surface/Suspended LED Downlight

- // Incorporates Tridonic LED and driver system
- // Multi-faceted 60° reflector as standard
- // Finished in RAL 9016 brilliant white as standard
- // Black and grey options available
- // 3000K and 4000K options
- // Integral emergency option
- // Dimming options available
- // Surface as standard (suspension mounting available)
- // IP20
- // CRI>80
- // 5-year warranty




### Construction

Our low-glare Enforce downlight has been selected for use in surface or suspended mounted applications and can be mounted directly onto a ceiling or BESA box. The powder-coated aluminium body provides corrosion resistance and excellent heat dissipation. The high-quality reflector is sealed by a clear diffuser. The size of the fitting allows for integral emergency controls.

### Typical Applications


Amenity Areas, Toilets, Tea-Points, Canteens, Receptions and General Office and Breakout Areas.

### Size Options



| Size    |         |
|---------|---------|
| Ø 150mm | H 165mm |

For optional features, please include the option code suffix with the product code when ordering.



| Product Code | LED Wattage | Lumen Output | Lumen/Watt | Colour Temperature |
|--------------|-------------|--------------|------------|--------------------|
| ENF8/3K      | 8W          | 892          | 111        | 3000K              |
| ENF8         | 8W          | 923          | 115        | 4000K              |
| ENF14/3K     | 14W         | 1506         | 109        | 3000K              |
| ENF14        | 14W         | 1561         | 113        | 4000K              |
| ENF19/3K     | 19W         | 2038         | 106        | 3000K              |
| ENF19        | 19W         | 2107         | 110        | 4000K              |

| Option Code | Description                        |
|-------------|------------------------------------|
| /M          | 3-Hour Maintained Emergency        |
| /MZ         | 3-Hour Maintained DALI Emergency   |
| /TD         | Mains Dimmable                     |
| /DALI       | DALI/DSI Driver                    |
| /TW         | Tuneable White                     |
| /BT         | Casambi Wireless Network (Inc Dim) |
| /9005       | RAL 9005 (Black)                   |
| /9006       | RAL 9006 (Grey)                    |
| /9010       | RAL 9010 (White)                   |
| /SUS        | Suspended Option                   |
| /MF25       | 25° Multi-Faceted Reflector        |
| /MF40       | 40° Multi-Faceted Reflector        |
| /SP40       | 40° Specular Reflector             |
| /SA50       | 50° Satin Reflector                |