

T-LINE 100MM

Decorative Suspended LED Tube 100mm

- // Available in multiple lengths
- // Colour options in 3000K/4000K/5000K
- // Custom shapes available subject to design
- // Incorporates European branded LED drivers
- // Up to 134 lumens per circuit watt
- // Opal polycarbonate diffuser
- // Tuneable white and RGBW options available
- // Dimmable and emergency options available
- // CRI>80, 50,000h life
- // End caps can be finished in your choice of RAL colour
- // Compatible with Casambi wireless control system
- // 5-year warranty



Construction

Our T-Line range uses an opal tubular polycarbonate diffuser with a hidden aluminium spine to suspend the luminaire. The fitting is supplied with a 1.5 metre clear flex as standard. The aluminium end caps are white as standard but can be finished in RAL colours of your choice.

Typical Applications

Receptions, Meeting Rooms, General Office Areas, Task Areas, Educational Facilities, Retail Units, Supermarkets, and Hospitals.

Size Options



Size	
L 595mm	Ø 100mm



Suspension Track



End Cap

Product Code	LED Wattage	Lumen Output	Lumen/Watt	Colour Temp.	Size
TLE100/595	18W	2404	134	4000K	595mm
TLE100/875	27W	3602	134	4000K	875mm
TLE100/1155	36W	4803	134	4000K	1155mm
TLE100/1435	44W	6004	134	4000K	1435mm
TLE100/1715	53W	7205	134	4000K	1715mm
TLE100/1995	62W	8406	134	4000K	1995mm
TLE100/2275	71W	9606	134	4000K	2275mm

Option Code	Description
/M	3 Hour Maintained Emergency
/MZ	3 Hour Maintained DALI Emergency
/DALI	DALI/DSI Dimmable Driver
/BTC	Casambi Dimmable
/3K	3000K LED
/5K	5000K LED
/RGB	Colour Changing LED
/TW	Tunable White LED

For coloured end caps, please state specific RAL colour.



For optional features, please include the option code suffix with the product code when ordering.