



LED

Norms: EN 60598-1, EN 60598-2-4



**PRODUCT DESCRIPTION**

**Areas of Application:** Housing, Offices, Hotel, Art and Culture Spaces.

**Mounting:** Desk.

**Light Distribution:** Direct.

**Light Source:** LED 4000K, CRI>90, 60.000h life (@L80, B10, Ta 25°C).

**Optical System:** Diffuser: Opal acrylic.

**Control Gear:** 24V Transformer.

**Materials:** Base and tube:metal; Top part: wood.

**Surface Finish:** Powder coated; Top part rosewood or powder coated.

DAZ - Opal acrylic diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC(mm)	kg	TouchDIM
	19	5	520	61	59%	Ø250x26x356	1,5	90306.L009.H

**COLOUR / FINISH**

Code	Description
W	White
G	Grey
B	Black
J	Rosewood

Note: Tube and base always in black.

**DETAILS**



TouchDIM

**OPTIONS**

**Colour temperature**



	2700K	Order code 2700
--	-------	--------------------

Example code for order: 90306.L009.E (TouchDIM) + W(COLOUR/FINISH) + 2700(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY

DIMENSIONS



TO SPECIFY:

Circular LED desk luminaire. Metal base and tube, epoxy-polyester powder coated, and top part in rosewood, white, grey or black finish. With opal acrylic diffuser DAZ. Standard version with LED strip 4000K, CRI>90 and 60.000h lifetime (@L80, B10, Ta 25°C). With TouchDim push-button. Optional 2700K version - as Indelague NOAH /D

We reserve the right to make technical changes without prior notice.  
Electrical/Optical data are subjected to a tolerance of +/-10%.