



LED

Norms: EN 60598-1, EN 60598-2-4



PRODUCT DESCRIPTION

Areas of Application: Housing, Offices, Hotel, Restaurant Services, Art and Culture spaces.

Mounting: Free-Standing.

Light Distribution: Indirect.

Light Source: LED 4000K, CRI>80, 50.000h lifetime (@L80, B10, Ta 25°C).

Optical System: Diffuser: Opal acrylic.

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Base and tube: metal; Top part: wood.

Surface Finish: Powder coated; Top part rosewood or powder coated.

DAZ - Opal acrylic diffuser

LED	UGR	W	Lm	Lm/W	η(%)	AxBxC(mm)	kg	HF
	10	31	4660	128	85	Ø400x26x1800	10	90307.L031.E

COLOUR / FINISH

Code	Description
W	White
G	Grey
B	Black
J	Rosewood

Note: Tube and base always in black.


DETAILS



Includes 3,50m cable and foot switch.

OPTIONS

Colour temperature



3000K


Order code
3000

Example code for order: 90307.L031.E (HF) + J(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY

DIMENSIONS



NOAH /F 31W
DAZ 4000K



AxBxC (mm)
Ø340x25x1800

TO SPECIFY:

Circular LED free-standing luminaire. Metal base and tube, epoxy-polyester powder coated, and top part in rosewood, white, grey or black finish. With opal acrylic diffuser DAZ. Standard version in 4000K LED, CRI>80 and 50.000h lifetime (@L80, B10, Ta 25°C). On/off push-button. Optional 3000K version - as Indelague NOAH /F

We reserve the right to make technical changes without prior notice.
Electrical/Optical data are subjected to a tolerance of +/-10%.