



LED

Norms: EN 60598-1, EN 60598-2-1



PRODUCT DESCRIPTION

Areas of Application: Commercial, Business areas, Private Houses, Art and Culture spaces. Offices, Public buildings, Hotel and Restaurant services.

Mounting: Surface.

Light Distribution: Direct.


Light Source: LED 4000K, CRI>90, MacAdam Step<3, 64.000h life (@L80, B10, Ta 25°C).

Control Gear: LED driver, 220-240VAC-50/60Hz.

Materials: Body: Extruded aluminium tube.

Surface Finish: Powder coated.

LIGHT+ - Opal diffuser

	LED	UGR	W	Lm	Lm/W	η(%)	AxB(mm)	kg	HF	DALI
		22	8	780	65	67	Ø95x206	1,2	90447.L008.E	-
		22	10	1100	70	64	Ø95x206	1,2	90447.L011.E	90447.L011.H
		25	13	1540	76	64	Ø95x206	1,2	90447.L015.E	90447.L015.H

COLOUR / FINISH


Code	Description
<input type="checkbox"/> W	White
<input checked="" type="checkbox"/> B	Black
<input type="checkbox"/> G	Grey

DIMENSIONS



OPTIONS

Colour temperature




3000K

Order code
3000

Example code for order: 90447.L015.E (HF) + W(COLOUR/FINISH) + 3000(OPTIONS)

We reserve the right to make technical changes without prior notice. Electrical/Optical data are subjected to a tolerance of +/-10%.

PHOTOMETRY



TO SPECIFY:

Circular LED downlight, with $\varnothing 95\text{mm}$ and IP54 for surface application. Extruded aluminium body, powder coated in epoxy-polyester in white, grey and black. With three possible light flux levels (780 lm, 1100 lm and 1540 lm). Standard version with LED 4000K, CRI>90, MacAdam Step<3 and 64.000h lifetime (@L80, B10, Ta 25°C). Optional DALI dimmable LED driver and 3000K. - as Roxo Lighting VEGA IP.