

HALO



Construction

The Halo is designed to be surface mounted or suspended to a single suspension point. Available in 5 different sizes and a wide variety of RAL colours. It is the ideal option when lighting a large open space or simply wanting to create a stunning feature. The versatility of the aluminium body and LED technology used allows for inclusion of many control options, including dimming, emergency options, wireless switching and scene-setting Casambi control technology.

- // Decorative surface/suspended LED luminaire
- // European-branded LED drivers
- // Up to 97 lumens per circuit watt
- // Direct/Indirect option available - 67% / 33% ratio
- // Extruded aluminium body
- // Colour-matched ceiling rose
- // 650mm, 950mm, 1250mm, 1550mm and 1950mm diameter body options
- // LED 4000K, 81,000h life
- // CRI>80 & CRI>90 options
- // Opal polycarbonate diffuser
- // Compatible with Casambi wireless control system
- // 5-year warranty

Typical Applications

General Office Areas, Conference Rooms, Reception Areas, Educational Facilities, Retail Units, Bars, Restaurants, Hotels and Leisure Facilities.

Size Options



Please note: These are external diameter measurements

SURFACE



SUSPENDED



HALO

Halo Surface and Suspended					
Product Code	LED Wattage	Lumen Output	Lumen/Watt	Colour Temp.	Size
HLO650	39W	3101	79	4000K	650 x 65 x 85mm
HLO950	57W	4652	81	4000K	950 x 65 x 85mm
HLO1250	75W	6203	82	4000K	1250 x 65 x 85mm
HLO1550	97W	7753	80	4000K	1550 x 65 x 85mm
HLO1950	115W	9304	81	4000K	1950 x 65 x 85mm
Halo Suspended Direct/Indirect - 67% / 33% Ratio					
HLD650	39W	4502	93	4000K	650 x 65 x 85mm
HLD950	56W	6986	97	4000K	950 x 65 x 85mm
HLD1250	73W	9315	95	4000K	1250 x 65 x 85mm
HLD1550	89W	11644	96	4000K	1550 x 65 x 85mm
HLD1950	112W	13972	97	4000K	1950 x 65 x 85mm

Halo Code Configurator

Choose your options to generate the full Halo order code

Section	Option Code	Description
1 - EMERGENCY	/M	Leave blank if no emergency Emergency
	/MZ	DALI Emergency
	/ND	Non Dimmable
2 - CONTROL	/DA	DALI Dimmable
	/BTC	Casambi Dimmable
3 - FINISH	/9016	RAL9016 White
	/9005	RAL9005 Black
	/RA	Any RAL Colour
4 - CCT	/4K	4000K
	/3K	3000K
5 - CRI	/80	CRI80
	/90	CRI90

FULL HALO CODE EXAMPLE:

HLO950/MZ/DA/9005/4K/90 = Halo Suspended Linear Light, 950mm, DALI Emergency, DALI Dim, Black RAL9005, 4000K, CRI90

Option Images



Ceiling Rose Selector

Choose your options to generate the full Ceiling Rose order code

Model	Ceiling Rose Dimensions (Ø x H)	Qty of hanging wires	Associated Halo Models
CR0	157mm x 32mm	None	Any if surface mounted
CR1	157mm x 32mm	3	650mm, 950mm
CR2	157mm x 32mm	4	1250mm
CR3	157mm x 32mm	5	1550mm
CR4	157mm x 32mm	6	1950mm

Ceiling Rose Configurator

Section	Option Code	Description
1 - EMERGENCY	/M	Leave blank if no emergency Emergency
	/MZ	DALI Emergency
	/ND	Non Dimmable
2 - CONTROL	/DA	DALI Dimmable
	/BTC	Casambi Dimmable
3 - FINISH	/9016	RAL9016 White
	/9005	RAL9005 Black
	/RA	Any RAL Colour
4 - SUSPENSION LENGTH	/2M	2 metre, standard
	/5M	5 metre

FULL CEILING ROSE CODE EXAMPLE:

CR4/MZ/BTC/9005/2M = 1950mm Halo Ceiling Rose, DALI Emergency, Casambi, Black RAL9005, 2M suspension