

M-LINE 54 - LOW GLARE DIRECT/INDIRECT

M-LINE®

- // Aluminium extruded sections in 15 standard lengths
- // Bespoke lengths and shapes available
- // 3m clear flex
- // Low UGR
- // Direct / Indirect light distribution (60:40 ratio)
- // Uniform light and controlled beam with specialised diffuser
- // Colour options in 3000K/4000K
- // Dimmable and emergency options available
- // Compatible with Casambi wireless technology
- // Incorporates European branded LED drivers
- // Energy efficient, 131 lm/W
- // Lifetime >80,000 h L80 B10
- // CRI>80
- // 5-year warranty



Construction

The M-Line 54 is a low glare, UGR19 compliant luminaire. The low UGR is achieved with a specialised polycarbonate diffuser. The suspended linear light fitting is designed with direct (60%) and indirect (40%) light distribution, perfect for highlighting exposed or feature ceilings while providing comfortable light exposure for task areas. Suspension is made simple using a single-point ceiling bracket with a 5m adjustable stainless steel wire system. The extruded aluminium profile is available in standard lengths up to 4523mm with bespoke lengths and shapes available to order upon request.

We are now sending out our M-Line products pre-flexed to make installation easy for you!

Typical Applications

General Office Areas, Conference Rooms, Educational Facilities, Retail Units, Healthcare Facilities, Hospitality and Leisure Facilities.

Dimensions



FULL CODE EXAMPLE:

MLD54/1437/MZ/DA/9005/4K/80 = M-Line 54 Low Glare Direct/Indirect Suspended Linear Light, 1437mm, Monitored Emergency, DALI Dim, Black RAL9005, 4000K, CRI>80

Product Code	LED Wattage	Lumen Output	Lumen/Watt	Colour Temp.	Length
MLD54/596	21W	2794	131	4000K	596mm
MLD54/876	32W	4191	131	4000K	876mm
MLD54/1157	43W	5588	131	4000K	1157mm
MLD54/1437	53W	6985	131	4000K	1437mm
MLD54/1718	64W	8382	131	4000K	1718mm
MLD54/1998	75W	9779	131	4000K	1998mm
MLD54/2279	85W	11176	131	4000K	2279mm
MLD54/2559	96W	12573	131	4000K	2559mm
MLD54/2840	107W	13970	131	4000K	2840mm
MLD54/3120	117W	15367	131	4000K	3120mm
MLD54/3411	128W	16764	131	4000K	3411mm
MLD54/3681	139W	18161	131	4000K	3681mm
MLD54/3962	149W	19558	131	4000K	3962mm
MLD54/4242	160W	20955	131	4000K	4242mm
MLD54/4523	171W	22352	131	4000K	4523mm

NOTE: Bespoke lengths available upon request in increments of 280mm

Product Configuration

Choose your options to generate the full order code

Section	Option Code	Description
1 - EMERGENCY		Leave blank if no emergency
	/M	Emergency
	/MZ	DALI Emergency
2 - CONTROL	/ND	Non Dimmable
	/DA	DALI Dimmable
	/D	1-10V Dimmable
	/BTC	Casambi Dimmable
	/9016	RAL9016 White
3 - FINISH	/9005	RAL9005 Black
	/9006	RAL 9006 Grey
	/4K	4000K LED
4 - CCT	/3K	3000K LED
5 - CRI	/80	CRI>80